



## Neat Cutting Oil

Neat cutting oils 11L - 41H are cutting oils blended from high Viscosity Index Base Oils and Speciality additives to work in conditions varying from tool, workpiece and type of machines.

Neat Cutting Oil recommended for machining ferrous as well as non ferrous metals in various manual and CNC machines, including robotic manufacturing and 3D printing.

### Typical Physical Characteristics (Selected Grades)

	Neat Cut Ferrous	Neat Cut non-Ferrous
Appearance	B & C	B & C
Specific Gravity @ 15 c	0.865	0.865
Viscosity Index Viscosity cSt @ 40°C	22	22
Viscosity Index Viscosity cSt @ 100°C	4.35	4.35
Emulsion	Immiscible	Immiscible

There are 12 different grades of Metal Working Fluids are available. Please contact us for a proper selection

Color Varies from Country to Country. Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. Advice and opinion noted herein are given in good faith and on the basis of the best information available, information is based on past history of the grade only and must not be construed as a guarantee of performance nor any legal liability is accepted by United Grease or any of its affiliates. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The Material Safety Data Sheet for this product is available with your nearest United Grease office or at [www.unitedgrease.com](http://www.unitedgrease.com). © United Grease and Lubricants Co LLC, 2022